



Clean Emissions Products Inc.

"Every Engine Deserves Clean Emissions"

Honda Catalytic Mufflers

Application: Honda GX120, GX160, GX200, GX240, GX270, GX340, GX390, GX630, GX670

Basic Catalyst & Housing

Stainless Steel Catalyst Core (15 Gram Pt Loading)

Stainless Steel Housing

Maximum Pressure Drop of < 2" H₂O

Direct Replacement to Honda OEM Mufflers



Effectiveness in Reducing Exhaust Emissions

CO (carbon monoxide) up to 99%

HC (hydrocarbons) up to 90%

NOx (oxides of nitrogen) up to 99%



Lifespan of Catalyst

8,000 to 12,000 Engine Hours



Maintenance

Designed to be maintenance-free when installed on a regularly maintained engine.
These catalytic mufflers are direct replacement to OEM Honda mufflers.

Operating Conditions for Successful Catalyst Performance

Exhaust temperature must be at least 250° C (482° F) and not exceed 750° C (1382° F)

Meets Federal/State/City Emission Standards

When installed this product will allow all Honda powered equipment to comply with
OSHA/EPA/PERP/MSHA emission standards.

The PRO Group



126 Calvary Street
Waltham, MA 02453
781.899.0790

280 Brookdale Drive
Springfield, MA 01104
413.732.8044

35 Oak Hill Way
Brockton, MA 02301
508.863.8026

10 Amflex Drive
Cranston, RI 02921
401.464.5000